

# PRODUCT DATASHEET QT-FIT 5/8 1X18...39

QUICKTRONIC® FIT 5/8 | ECG for FL and CFL, not dimmable



#### Areas of application

- Open-plan offices, corridors and storage rooms
- Public buildings
- Strip lighting
- Suitable for emergency lighting (DC operation)
- Suitable for luminaires of protection class I
- Modernization of existing systems

#### Product benefits

- Long lamp life
- No adverse effect from frequent on/off switching
- Automatic restart after lamp replacement
- Perfect lamp start for applications with motion sensors
- VDE/VDE EMC certified system
- Very high energy efficiency due to cut-off technology

## Product features

- Supply voltage: 220...240 V
- Line voltage: 198...264 V
- $-\,$  Line frequency: 50 Hz | 60 Hz
- Lamp start with optimum filament preheating

- Energy Efficiency Index EEI: A2
- Automatic shutdown of defective lamps and at end of life (EoL T.2)
- Lamp operation: to EN 60929
- Safety: to EN 61347-2-3

## TECHNICAL DATA

## Electrical data

Nominal wattage	42.00 W
Nominal voltage	220240 V
Input voltage AC	198264 V
Input voltage DC	185264 V <sup>1)</sup>
U-OUT (working voltage)	430 V
Inrush current	24 A
Mains frequency	50/60 Hz
Max. ECG no. on circuit breaker 10 A (B)	17 2)
Max. ECG no. on circuit breaker 16 A (B)	28 <sup>2)</sup>
Operating frequency	4050 kHz

<sup>1)</sup> Minimum voltage for lamp ignition: 198 V, 185...198 V for maximum 1 h  $\,$ 

# Light technical data

Starting time	2 \$
Dimensions & Weight	

Length	280.00 mm
Mounting hole spacing, length	270,0 mm
Width	30.00 mm
Height	21.00 mm
Cable cross-section, input side	0.51.5 mm <sup>2</sup> 1)
Cable cross-section, output side	0.51.5 mm <sup>2</sup> 1)
Product weight	154.00 g

<sup>1)</sup> Solid leads

## Colors & materials

Casing material	Metal
Body material	Metal

# Temperatures & operating conditions

Ambient temperature range	-15+50 °C
Maximum temperature at tc test point	75 °C

<sup>2) &</sup>lt;sub>Type B</sub>

Max.housing temperature in case of fault	110 °C
Permitted rel. humidity during operation	585 % <sup>1)</sup>

<sup>1)</sup> Maximum 56 days/year at 85 %

# Lifespan

ECG lifetime	50000 h
--------------	---------

# Capabilities

Dimmable	No
Max. cable length to lamp/LED module	2.0 m / 1.0 m
Suitable for fixtures with prot. class	1
End of lamp life safety shutdown	EOL T.2

## Certificates & Standards

Approval marks – approval	CE / VDE / ENEC 10 / VDE-EMC
Standards	Acc. to EN 61347-2-3/IEC 61347-2-3 / Acc. to EN 55015:2006 + A1:2007 + A2:2009 / Acc. to EN 61000-3-2/IEC 61000-3-2 / Acc. to EN 61547/IEC 61547
Protection class	1
Type of protection	IP20
Energy efficiency class	A2
EEI – Energy Label	A2

## LOGISTICAL DATA

Temperature range at storage -40+85 °C	Temperature range at storage	
--	------------------------------	--

## DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	592455_EAC QT-FIT 5/8
POF	Declarations of conformity	346515_CE Declaration QT-FIT 5_8
POF	Declarations of conformity	339525_Declaration of Conformity (GB)
PDF	Certificates	554891_EAC PT family

	Documents and certificates	Document name
POF	Certificates	346514_EMC QT-FIT 5_8
POF	Certificates	346513_ENEC QT-FIT 5_8
POF	Product family datasheet	346488_Familiendatenblatt QT-FIT 5_8

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321873927	Unpacked 1		154.00 g	
4008321873934	Shipping box 20	310 mm x 238 mm x 98 mm	3221.00 g	7.23 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.