

PRODUCT DATASHEET DALI Coupler Pushb G2

DALI COUPLER PB G2 | DALI-2 pushbutton coupler to integrate standard switches in DALI systems



Areas of application

- Suitable for installation in flush-type boxes
- Individual offices
- Classrooms
- Conference rooms
- Production and assembly facilities

Product benefits

- Standard pushbuttons/switches can be used
- DALI-2 certified
- DALI Bus powered (No mains connection necessary)
- Multiple couplers connectable to the same DALI line

Product features

- DALI pushbutton coupler
- 4 floating inputs

TECHNICAL DATA

Electrical data

Nominal wattage	0.10 W
Nominal voltage	16 V
Mains frequency	0 Hz

Dimensions & Weight

Length	43.00 mm
Width	43.00 mm
Height	21.00 mm
Product weight	25.00 g

Colors & materials

Temperatures & operating conditions

Capabilities

Dimmable	No
Dimming interface	DALI-2
Type of installation	Integrated in flush device box

Certificates & Standards

Approval marks – approval	CE
Protection class	П
Type of protection	IP20

DOWNLOAD DATA

Documents and certificates User instruction / safety instructions		Document name	
		DALI COUPLER PUSHB G2	
PDF	Declarations of conformity	DALI COUPLER PUSHB G2	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume	
--------------	------------------------------	--------------------------------------	--------------	--------	--

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4062172087575	Folding box	81 mm x 81 mm x 46 mm	42.00 g	0.30 dm ³
4062172087582	Shipping box 60	344 mm x 254 mm x 278 mm	3187.00 g	24.29 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.