

PRODUCT DATASHEET LS AY SUP -CSW/P2/500

Connectors for LED Strips Superior Class | Connectors for LED Strips Superior Class

Areas of application

- General outdoor illumination





Product benefits

- Easy installation of connector, no manual wiring required
- Tool-free installation

TECHNICAL DATA

Electrical data

| Nominal voltage | 25 V |
|-----------------|---------|
| Nominal current | 5000 mA |

Dimensions & Weight

| Length | 519.6 mm |
|---------------------------------|----------------------|
| Cable length | 500 mm |
| Width | 9.8 mm |
| Height | 5.7 mm |
| Cable cross-section, input side | 0.34 mm ² |
| Product weight | 7.00 g |

Colors & materials

| Product color White |
|---------------------|
|---------------------|

Temperatures & operating conditions

| Ambient temperature range | -35+75 °C |
|--------------------------------|-----------|
| Temperature range in operation | -35+75 °C |

Certificates & Standards

| Type of protection | IP00 |
|--------------------|------|
| | |

LOGISTICAL DATA

| Temperature range at storage -5+55 °C |
|---------------------------------------|
|---------------------------------------|

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075304505 | BAG 2 | 80 mm x 120 mm x 5 mm | 15.00 g | 0.05 dm ³ |
| 4058075304512 | Shipping box 100 | 213 mm x 213 mm x 215 mm | 1132.00 g | 9.75 dm ³ |
| 4058075304529 | Shipping box 400 | 439 mm x 439 mm x 233 mm | 5126.00 g | 44.90 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.