

PRODUCT DATASHEET LS AY SUP - CSW/P3/50

Connectors for TW LED Strips | Connectors for TW LED Strips



Areas of application

- General indoor illumination

Product benefits

- Easy installation of connector, no manual wiring required
- Tool-free installation

TECHNICAL DATA

Electrical data

Nominal voltage	036 V
Nominal current	5000 mA

Dimensions & Weight

Length	24.3 mm
Cable length	50 mm
Width	14.6 mm
Height	7.7 mm
Cable cross-section, input side	0.350.75 mm ²
Product weight	5.8 g

Colors & materials

Product color	Transparent

Temperatures & operating conditions

Ambient temperature range	-20+55 °C
Temperature range in operation	-20+55 °C

Certificates & Standards

Type of protection	IP00

LOGISTICAL DATA

Temperature range at storage	-35+85 °C
------------------------------	-----------

DOWNLOAD DATA

	Documents and certificates	Document name
POF	Declarations of conformity	LED STRIP ACCESSORIES

Tender texts	Document name
Tender documents	Connectors for TW LED Strips CSWP350-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075451384	BAG 2	80 mm x 120 mm x 5 mm	12.60 g	0.05 dm ³

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075451391	Shipping box 100	250 mm x 100 mm x 250 mm	778.00 g	6.25 dm ³
4058075451407	Shipping box 1,000	520 mm x 520 mm x 270 mm	21842.00 g	73.01 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.