

PRODUCT DATASHEET

LM RETROFIT C ECO 24 W/840

LEDVANCE Retrofit Circular Module | LED Modules with integrated optics and driver



Areas of application

- Hallways, corridors

Product benefits

- Compact, lightweight
- Self-adhesive backing for simple installation

Product features

- LED light engine with integrated driver
- Color rendering index $R_a: > 80$
- Input voltage: 220...240 V_{AC}
- LED replacement for luminaires that use traditional circular fluorescent lamps

TECHNICAL DATA

Electrical data

Nominal wattage	24.00 W
Construction wattage	24.00 W
Nominal voltage	220...240 V
Type of current	AC
Power factor λ	> 0.50

Photometrical data

Luminous efficacy	90 lm/W
Luminous flux	2200 lm
Color temperature	4000 K
Color rendering index Ra	80
Light color (designation)	Cool White

Light technical data

Beam angle	160 °
------------	-------

Dimensions & Weight



Length	228.00 mm
Width	228.00 mm
Height	24.00 mm
Product weight	131.00 g

Temperatures & operating conditions

Ambient temperature range	-20...+45 °C
Maximum temperature at tc test point	75 °C

Capabilities

Dimmable	No
----------	----

LOGISTICAL DATA

Temperature range at storage	-25...+85 °C
------------------------------	--------------

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075189935	Folding box 1	236 mm x 30 mm x 236 mm	182.00 g	1.67 dm ³
4058075189942	Shipping box 10	310 mm x 245 mm x 245 mm	2140.00 g	18.61 dm ³
4058075189959	Shipping box 60	770 mm x 325 mm x 520 mm	14435.00 g	130.13 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.