

PRODUCT DATASHEET

DL COMFORT DN 155 18 W 3CCT IP54 WT

DOWNLIGHT COMFORT | Downlights with adjustable white light colors



PERFOR-
MANCE
CLASS

Areas of application

- Direct replacement for luminaires with compact fluorescent lamps
- General illumination
- Bathrooms
- Kitchens
- Offices
- Corridors
- Foyers
- Shops
- Stairways

Product benefits

- Three light color in one luminaire: Warm White, Cool White, Daylight White
- Simple installation thanks to integrated driver
- Easy installation with fast connection
- 5 years guarantee

Product features

- Three light colors selectable via slide switch
- Type of protection: IP54
- Connector box with push wire terminal for tool-free connection
- Through wiring possible



TECHNICAL DATA**Electrical data**

Nominal wattage	18.00 W
Nominal voltage	100...277 V
Mains frequency	50...60 Hz
Nominal current	200 mA
Inrush current	55 A
Inrush current time T_{h50}	100 μ s
Max. number of luminaires per miniature circuit breaker B16	15
Max. number of luminaires per miniature circuit breaker C10	12
Max. number of luminaires per miniature circuit breaker C16	19
Power factor λ	> 0.90
Total harmonic distortion	< 20 %
Protection class	I
Operating mode	Integrated LED driver


Photometrical data

Luminous flux	1040...1620 lm ¹⁾
Luminous efficacy	85 lm/W ²⁾
Color temperature	3000...5700 K ³⁾
Light color (designation)	Warm White / Cool White / Cool Daylight
Color rendering index Ra	> 80
Standard deviation of color matching	< 5 sdcm
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0
Beam angle	60 °
UGR	< 22


1) Luminous flux dependent on selected color temperature: 1040 lm@3000 K/1620 lm@4000 K/1470 lm@5700 K

2) Value at 5700 K, different for other color temperatures

3) Color temperature switchable: 3000 K, 4000 K, 5700 K




DL COMFORT DN155 18W3CCT 60DEG WT-4000K



DL COMFORT DN155 18W3CCT 60DEG WT-4000K

Dimensions & Weight

Diameter	172.00 mm
Height	95.00 mm
Product weight	350.00 g



DL COMFORT DN155 18W

Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum
Cover material	Polymethylmethacrylate (PMMA)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+45 °C
Type of connection	Screwless terminal, 2-Pole
Type of protection	IP54/IP20
Protection class IK (shock resistance)	IK03
Dimmable	No
Mounting type	Recessed
Mounting location	Ceiling
Application environment	Indoor
Mounting diameter	155,0 mm
Mounting depth	125 mm

Lifespan

Lifespan L70/B50 at 25 °C	50000 h ¹⁾
Lifespan L80/B10 at 25 °C	43000 h ¹⁾
Lifespan L80/B50 at 25 °C	45000 h
Lifespan L90/B10 at 25 °C	30000 h
Number of switching cycles	50000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Standards	CE / CB / ENEC / TÜV SÜD / RoHS
Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable

Safety advice

– All electrical connections must be made by a qualified person.

- Caution, risk of electric shock.
- The luminaires are not suitable for covering with thermally insulated material.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA





Documents and certificates		Document name
	User instruction / safety instructions	UI Downlight Comfort
	On-Pack-Info	Legal Insert Downlight LED ALU+Comfort
	Declarations of conformity	EU Declaration of Conformity DOWNLIGHT Comfort LEDV
	Declarations of conformity	Attestation-of-Conformity DOWNLIGHT Comfort TÜV
Photometric and lighting design files		Document name
	IES file (IES)	DL COMFORT DN155 18W3CCT 60DEG WT-4000K
	LDT file (Eulumdat)	DL COMFORT DN155 18W3CCT 60DEG WT-4000K
	UGR file (UGR table)	DL COMFORT DN155 18W3CCT 60DEG WT-4000K
	Light distribution curve type cone	DL COMFORT DN155 18W3CCT 60DEG WT-4000K
	Light distribution curve type polar	DL COMFORT DN155 18W3CCT 60DEG WT-4000K

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075270930	Folding box 1	195 mm x 195 mm x 140 mm	430.00 g	5.32 dm³
4058075270947	Shipping box 8	410 mm x 410 mm x 300 mm	4156.00 g	50.43 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.