

PRODUCT DATASHEET

SF BLKH 250 10W/4000K BK IP65

SURFACE BULKHEAD 250 ON/OFF | Robust wall and ceiling luminaire with IP65 protection



Areas of application

- Direct replacement for luminaires with fluorescent lamps
- Corridors, stairways, entrance areas
- Passages, underpasses
- Public areas

Product benefits

- Suitable for use in dusty and damp locations thanks to high IP rating
- Suitable for use in public areas thanks to high IK rating
- Multiple mounting patterns for convenient installation
- Separate covers available for an aesthetic and functional product design
- 5 years guarantee
- Energy savings of up to 50 % (compared to luminaires that use fluorescent lamps)

Product features

- UV-stabilized polycarbonate (PC) housing, PC-diffuser
- Impact resistance: IK10
- Push wire terminal for tool-free connection
- Through wiring possible
- Type of protection: IP65
- Luminous flux: up to 800 lm
- High luminous efficacy: up to 80 lm/W



- Lifetime (L70/B50) up to 50,000 h (at 25 °C)
- Ambient temperature in operation: -20...+40 °C


TECHNICAL DATA

Electrical data


Nominal wattage	8.20 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	350 mA
Inrush current	4.52 A
Inrush current time T_{h50}	50 μ s
Max. number of luminaires per miniature circuit breaker B16	94
Max. number of luminaires per miniature circuit breaker C10	75
Max. number of luminaires per miniature circuit breaker C16	120
Power factor λ	≥ 0.5
Total harmonic distortion	< 10 %
Protection class	II
Operating mode	Integrated LED driver

Photometrical data

Luminous flux	800 lm
Luminous efficacy	80 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	> 80
Standard deviation of color matching	< 5 sdc _m
Luminous intensity	-
Low flicker	Yes
Flickering metric (Pst LM)	-
Stroboscope effect metric (SVM)	-
Photobiological safety group acc. to EN62778	RG0
Beam angle	120 °




SF BLKH 250 10W4000K BK IP65 LEDV LDT



SF BLKH 250 10W4000K BK IP65 LEDV LDT

Dimensions & Weight

Diameter	250.00 mm
Height	70.00 mm
Product weight	520.00 g



Materials & Colors

Product color	Black
Housing color	Black
Body material	Polycarbonate (PC)

Cover material	Polycarbonate (PC)
Light emitting surface material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	850 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Type of connection	Screwless terminal
Type of protection	IP65
Protection class IK (shock resistance)	IK10
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling / Wall
Application environment	Indoor
With light source	Yes
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	50000 h ¹⁾
Lifespan L80/B10 at 25 °C	35000 h ¹⁾
Lifespan L80/B50 at 25 °C	35000 h
Lifespan L90/B10 at 25 °C	20000 h
Number of switching cycles	100000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Standards	CE / CB
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable

Additional product data

Number of illuminants	-
-----------------------	---

Accessories Optional

Product image	Product name	EAN
	SF BLKH EYELID 250 BK	4058075375505
	SF BLKH RING 250 BK	4058075399358

EQUIPMENT / ACCESSORIES

- Additional cover rings in different designs available
- Mounting screws and dowels included

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	SURFACE BULKHEAD
	Declarations of conformity	SF BULKHEAD
Photometric and lighting design files		Document name
	IES file (IES)	SF BLKH 250 P 10W 840 BK IP65
	LDT file (Eulumdat)	SF BLKH 250 P 10W 840 BK IP65
	UGR file (UGR table)	SF BLKH 250 10W4000K BK IP65 LEDV LDT
	Light distribution curve type cone	SF BLKH 250 10W4000K BK IP65 LEDV LDT
	Light distribution curve type polar	SF BLKH 250 10W4000K BK IP65 LEDV LDT


Tender texts		Document name
 Tender documents		SURFACE BULKHEAD 250 ONOFF 10W4000K BK IP65-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075374904	Folding box 1	74 mm x 272 mm x 262 mm	602.00 g	5.27 dm³
4058075374911	Shipping box 8	550 mm x 285 mm x 315 mm	5398.00 g	49.38 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.