

PRODUCT DATASHEET LED BULKHEAD 10 W/6500 K

LED BULKHEAD | Wall luminaires



Areas of application

- Indoor and outdoor
- Residential sector
- Hospitality
- Retail
- Hotels, restaurants, shops

Product benefits

- Easy and quick installation

Product features

- Type of protection: IP65
- Housing made of durable polycarbonate
- Suitable for wall mounting
- Diffuser made of opal polycarbonate
- Lifetime up to 15,000 h



TECHNICAL DATA

Electrical data


Nominal wattage	10.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	50.000 mA
Power factor λ	> 0.95

Photometrical data

Luminous flux	850 lm
Luminous efficacy	85 lm/W
Color temperature	6500 K
Light color (designation)	Daylight
Color rendering index Ra	80
Beam angle	120 °

Dimensions & Weight

Length	232.00 mm
Width	108.00 mm
Height	45.00 mm
Product weight	275.00 g



LED bulkhead wall light 10W

Materials & Colors

Product color	White
Housing color	White
Body material	Plastic
Cover material	Plastic

Application & Mounting

Type of connection	Cable/Connector
Type of protection	IP65
Dimmable	No
Mounting type	Surface
Mounting location	Wall
Replaceable light source	No

Certificates & Standards

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075283398	Folding box 1	237 mm x 110 mm x 59 mm	371.00 g	1.54 dm ³
4058075283404	Shipping box 10	600 mm x 245 mm x 130 mm	4077.00 g	19.11 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.