

# PRODUCT DATASHEET LED Value Batten 600 6 W 6500 K

# LED VALUE BATTEN | LED batten luminaires



#### Areas of application

- Offices
- Residential interiors
- Hotels, restaurants, shops

## Product benefits

- Long lifetime thanks to LED technology
- Mercury-free technology
- Uniform room illumination
- Accessories for flexible mounting options included

#### Product features

- Protection class: II
- Color rendering index  $R_a$ :  $\geq 80$
- Type of protection: IP20
- $-\,$  Lifetime (L70/B50): up to 20,000 h



## **TECHNICAL DATA**

## Electrical data


| Nominal wattage        | 6.00 W   |
|------------------------|----------|
| Nominal voltage        | 100240 V |
| Mains frequency        | 5060 Hz  |
| Power factor $\lambda$ | > 0.90   |
| Protection class       | П        |

# Photometrical data

| Luminous flux                        | 600 lm   |
|--------------------------------------|----------|
| Luminous efficacy                    | 100 lm/W |
| Color temperature                    | 6500 K   |
| Light color (designation)            | Daylight |
| Color rendering index Ra             | ≥80      |
| Standard deviation of color matching | ≤5 sdcm  |
| Beam angle                           | 120°     |

# Dimensions & Weight

| Length         | 600.00 mm |
|----------------|-----------|
| Width          | 23.00 mm  |
| Height         | 35.00 mm  |
| Product weight | 150.00 g  |



LEDVAL BATTEN 2F

Materials & Colors

| Product color   | White                        |
|-----------------|------------------------------|
| Housing color   | White                        |
| Body material   | Polycarbonate (PC) Polyvenyl |
| Mercury content | 0.0 mg                       |

## **Application & Mounting**

| Ambient temperature range    | -10+40 °C |
|------------------------------|-----------|
| Temperature range at storage | -40+70 °C |
| Type of protection           | IP20      |
| Dimmable                     | No        |
| Mounting location            | Wall      |
| Application environment      | Indoor    |
| Replaceable light source     | No        |

## Lifespan

| Number of switching cycles    | 15000 |
|-------------------------------|-------|
| Training of a mile in ignored |       |

#### Certificates & Standards

|--|

## **EQUIPMENT / ACCESSORIES**

- External cable (1.5 m) and corner connection (0.25 m) included

#### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075219823 | Folding box<br>1             | 687 mm x 42 mm x 47 mm               | 229.00 g     | 1.36 dm <sup>3</sup>  |
| 4058075219830 | Shipping box<br>30           | 705 mm x 275 mm x 267 mm             | 7814.00 g    | 51.76 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.