

PRODUCT DATASHEET LED Value Batten 1200 13 W 6500 K

LED VALUE BATTEN | LED batten luminaires



Areas of application

- Offices
- Residential interiors
- Hotels, restaurants, shops

Product benefits

- Long lifetime thanks to LED technology
- Mercury-free technology
- Uniform room illumination
- Accessories for flexible mounting options included

Product features

- Protection class: II
- Color rendering index R_a : ≥ 80
- Type of protection: IP20
- Lifetime (L70/B50): up to 20,000 h



TECHNICAL DATA

Electrical data


Nominal wattage	13.00 W
Nominal voltage	100240 V
Mains frequency	5060 Hz
Power factor λ	> 0.90
Protection class	П

Photometrical data

Luminous flux	1300 lm
Luminous efficacy	100 lm/W
Color temperature	6500 K
Light color (designation)	Daylight
Color rendering index Ra	≥80
Standard deviation of color matching	≤5 sdcm
Beam angle	120°

Dimensions & Weight

Length	1180.00 mm
Width	23.00 mm
Height	35.00 mm
Product weight	290.00 g



LEDVAL BATTEN 4F

Materials & Colors

Product color	White
Housing color	White
Body material	Polycarbonate (PC) Polyvenyl

Application & Mounting

Ambient temperature range	-10+40 °C
Temperature range at storage	-40+70 °C
Type of protection	IP20
Dimmable	No
Mounting location	Wall
Application environment	Indoor
Replaceable light source	No

Lifespan

Number of switching cycles	15000

Certificates & Standards

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075219861	Folding box 1	1,297 mm x 42 mm x 47 mm	432.00 g	2.56 dm ³
4058075219878	Shipping box 30	1,315 mm x 275 mm x 267 mm	14419.00 g	96.55 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.