

PRODUCT DATASHEET TruSys® PFM ENERGY RAIL 5P 3000

TruSys® PERFORMANCE ENERGY RAIL 5 POLE | 5-pole mounting rail



Areas of application

- Industry halls, high rack warehouse, garages, hardware stores

Product benefits

- Simple installation
- High flexibility thanks to two available lengths (1500 mm, 3000 mm and 1500 mm end rail)

Product features

- Through wired with 5 core cable
- Different lenghts available
- Electrical connection internal at the first luminaire, no external connection unit required
- Steel-sheet housing
- End-Rail without electrical and mechanical connectors



TECHNICAL DATA

Dimensions & Weight

Length	3150 mm
Width	70.2 mm
Height	38.8 mm
Product weight	3260.00 g



Materials & Colors

Product color	White		
Application & Mounting			
Ambient temperature range	-25+60 °C		
Type of protection	IP20		
Mounting type	Surface		
Mounting location	Ceiling		

Certificates & Standards

Replaceable light source

With light source

Standards	CE

No

No

EQUIPMENT / ACCESSORIES

- Various accessories available

DOWNLOAD DATA

	Documents and certificates	Document name
POF	User instruction / safety instructions	User Instruction Trunking System

CAD/BIM files	Document name
CAD STEP 3D	TRUSYS PFM ER 3000
Tender texts	Document name

TruSys PERFORMANCE ENERGY RAIL 5 POLE 3000-EN

LOGISTICAL DATA

Tender documents

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075299498	Shipping box 10	3,230 mm x 460 mm x 170 mm	35083.00 g	252.59 dm ³
4058075354777	Shipping box	3,170 mm x 88 mm x 56 mm	3797.00 g	15.62 dm ³
4058075299498	Shipping box 10	3,230 mm x 460 mm x 170 mm	35083.00 g	252.59 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.