

PRODUCT DATASHEET

LED ECO FLOODLIGHT 20 W 6500 K Gray

LED ECO FLOODLIGHT | LED floodlight luminaires



Areas of application

- Architectural lighting
- Landscape lighting
- Billboard lighting
- Industrial and storage facilities

Product benefits

- SMD LED design for high product reliability
- Reduced windage area thanks to slim design
- Frosted cover made of tempered glass for uniform illumination
- Dust and water protection according to IP65

Product features

- Color rendering index R_a : > 80
- Luminaire efficacy: up to 85 lm/W
- Die-cast aluminum housing
- Impact resistance: IK06
- Lifetime (L70/B50): up to 30,000 h
- 0.5 m cable between luminaires



TECHNICAL DATA

Electrical data


Nominal wattage	20.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Power factor λ	0.90
Protection class	I
Operating mode	Integrated LED driver

Photometrical data

Luminous flux	1700 lm
Luminous efficacy	85 lm/W
Color temperature	6500 K
Light color (designation)	Daylight
Color rendering index Ra	≥ 80
Standard deviation of color matching	≤ 5 sdc _{cm}
Beam angle	115 °

Dimensions & Weight

Length	137.00 mm
Width	111.00 mm
Height	24.00 mm
Product weight	330.00 g
Cable length	500 mm



LDECO FL 20W

Materials & Colors

Product color	Gray
Housing color	Gray
Body material	Aluminum

Cover material	GLASS
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+50 °C
Temperature range at storage	-30...+70 °C
Type of protection	IP65
Protection class IK (shock resistance)	IK06
Dimmable	No
Mounting type	Surface
Mounting location	All surfaces / Wall
Application environment	Outdoor

Lifespan


Lifespan L70/B50 at 25 °C	30000 h ¹⁾
Number of switching cycles	30000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

DOWNLOAD DATA

Photometric and lighting design files		Document name
	IES file (IES)	LDECO FL 20W 865

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075230811	Folding box 1	140 mm x 28 mm x 130 mm	364.00 g	0.51 dm ³
4058075230828	Shipping box 20	310 mm x 290 mm x 145 mm	7960.00 g	13.04 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.