

# PRODUCT DATASHEET

## LED ECO FLOODLIGHT 50 W 4000 K Gray

LED ECO FLOODLIGHT | LED floodlight luminaires



### Areas of application

- Architectural lighting
- Landscape lighting
- Billboard lighting
- Industrial and storage facilities

### Product benefits

- SMD LED design for high product reliability
- Reduced windage area thanks to slim design
- Frosted cover made of tempered glass for uniform illumination
- Dust and water protection according to IP65

### Product features

- Color rendering index  $R_a$ : > 80
- Luminaire efficacy: up to 85 lm/W
- Die-cast aluminum housing
- Impact resistance: IK06
- Lifetime (L70/B50): up to 30,000 h
- 0.5 m cable between luminaires



TECHNICAL DATA

Electrical data


Nominal wattage	50.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Power factor $\lambda$	0.90
Protection class	I
Operating mode	Integrated LED driver

Photometrical data

Luminous flux	4250 lm
Luminous efficacy	85 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	$\geq 80$
Standard deviation of color matching	$\leq 5$ sdc <sub>cm</sub>
Beam angle	115 °

Dimensions & Weight

Length	209.00 mm
Width	165.00 mm
Height	28.00 mm
Product weight	765.00 g
Cable length	500 mm



Materials & Colors

Product color	Gray
Housing color	Gray
Body material	Aluminum

Cover material	GLASS
Mercury content	0.0 mg

### Application & Mounting

Ambient temperature range	-20...+50 °C
Temperature range at storage	-30...+70 °C
Type of protection	IP65
Protection class IK (shock resistance)	IK06
Dimmable	No
Mounting type	Surface
Mounting location	All surfaces / Wall
Application environment	Outdoor
Replaceable light source	No

### Lifespan


Lifespan L70/B50 at 25 °C	30000 h <sup>1)</sup>
Number of switching cycles	30000

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### Certificates & Standards

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

### DOWNLOAD DATA

Photometric and lighting design files		Document name
	IES file (IES)	LDECO FL 50W 840

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075340619	Folding box 1	215 mm x 33 mm x 187 mm	831.00 g	1.33 dm <sup>3</sup>
4058075340626	Shipping box 10	380 mm x 245 mm x 235 mm	8981.00 g	21.88 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.