


# PRODUCT DATASHEET Orbis IP44 Sensor 400mm 25W

ORBIS® IP44 | Splash-proof LED ceiling luminaire with sensor



#### Areas of application

- Entrances / Hallways
- Bathrooms
- Ceiling and wall surface mounting
- Outdoor use (roofed areas) in residential sector

#### **Product benefits**

- Very homogenous light
- Easy and quick installation

#### **Product features**

- Ceiling luminaire with advanced LED technology
- Circular light emission
- Type of protection: IP44
- Versions with movement and daylight sensor available (microwave sensor)



# TECHNICAL DATA

## Electrical data

Nominal wattage	25.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	185 mA
Inrush current	9.1 A
Max. number of luminaires per miniature circuit breaker B16	18
Max. number of luminaires per miniature circuit breaker C10	18
Max. number of luminaires per miniature circuit breaker C16	29
Power factor λ	> 0.5
Protection class	I I
Operating mode	External LED driver

## Photometrical data

Luminous flux	1800 lm
Total luminous flux of contained light sources	2700 lm
Luminous efficacy	80 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 80
Standard deviation of color matching	< 6 sdcm
Photobiological safety group acc. to EN62778	RG1
Photobiological safety group acc. to EN62471	RG0
Beam angle	120°

# Dimensions & Weight

Diameter	400 mm
Height	83.00 mm
Product weight	695.00 g

## Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum
Cover material	Polycarbonate (PC)

Mercury content	0.0 mg	
Application & Mounting		
Ambient temperature range	-20+40 °C	
Temperature range at storage	-20+70 °C	
Type of connection	Terminal, 3-Pole (L, N, PE)	
Type of protection	IP44	
Protection class IK (shock resistance)	IK03	
Dimmable	No	
Mounting type	Surface	
Mounting location	Ceiling	
Application environment	Indoor	
With light source	Yes	
Replaceable light source	No	
Lifespan		
Lifespan L70/B50 at 25 °C	25000 h <sup>1)</sup>	

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

## Sensor

Number of switching cycles

Type of sensor	Light / Motion
Sensor technology	Microwave
Sensor detection angle	125 °
Detection range of motion sensor	14 m
Detection threshold of daylight sensor	2 lx / 10 lx / 50 lx

12500

# **Emergency lighting**

Type of emergency light operation	Non-maintained	
Luminous flux in maintained operation mode	-	
Luminous flux in emergency operation mode	-	

# Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No

# **EQUIPMENT / ACCESSORIES**

- Complete mounting and connecting accessories included

#### Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

#### **DOWNLOAD DATA**

Documents and certificates Document name		Document name
User instruction / safety instructions ORBIS IP44		ORBIS IP44
Declarations of conformity  ORBIS IP44 400MM 25W 830 S		ORBIS IP44 400MM 25W 830 SENSOR LEDV
PDF	Declarations of conformity UKCA	ORBIS IP44 SENSOR

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075651852	Folding box 1	94 mm x 429 mm x 429 mm	836.00 g	17.30 dm <sup>3</sup>
4058075651869	Shipping box 5	482 mm x 447 mm x 459 mm	5129.00 g	98.89 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.