

# PRODUCT DATASHEET

## Neon Flex IP44 3M 830

NEON FLEX | Decorative warm white LED Strips for outdoor use with homogeneous illumination



---

### Areas of application

- Gardens, balconies and other outdoor areas
- Indirect and direct lighting
- Living areas

---

### Product benefits

- Easy and quick installation

---

### Product features

- Flexible, bendable LED strips
- Type of protection: IP44

TECHNICAL DATA

Electrical data


Nominal wattage	19.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	160.000 mA
Power factor $\lambda$	> 0.50
Protection class	II
Operating mode	External LED driver

Photometrical data

Luminous flux	1000 lm
Total luminous flux of contained light sources	1860 lm
Luminous efficacy	53 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 80
Photobiological safety group acc. to EN62778	RG0
Beam angle	110 °

Dimensions & Weight

Length	3000.00 mm
Width	13.50 mm
Height	6.70 mm
Product weight	435.00 g



NEON FLEX 3M 3000K IP44

Materials & Colors

Body material	Silicone
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting

Type of connection	Plug type C (EU)
Type of protection	IP44

Dimmable	No
Mounting type	Surface
Application environment	Outdoor
With light source	Yes
Replaceable light source	No

### Lifespan

Lifespan L70/B50 at 25 °C	30000 h <sup>1)</sup>
Number of switching cycles	15000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### Certificates & Standards

Standards	CE
-----------	----



### EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

### Safety advice

- To reduce the risk of strangulation the flexible wiring connected to this luminaire shall be effectively fixed to the wall if the wiring is within arm's reach.

### DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	NEON Flex Warm White
	Declarations of conformity	NEON FLEX 3M and 5M

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854449116	Folding box 1	67 mm x 252 mm x 253 mm	543.00 g	4.27 dm <sup>3</sup>
4099854449123	Shipping box 4	285 mm x 270 mm x 310 mm	2639.00 g	23.85 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.