

# PRODUCT DATASHEET SENSOR WALL 360DEG IP55 DG

SENSOR WALL 360DEG | Stand-alone motion and light sensors for wall mounting with 360° detection range

#### Areas of application

- Outdoor
- Corridors, entrance areas
- Garages
- Basement
- Arcade passage
- Various mounting options



#### **Product benefits**

- Sensor for optimized energy savings

#### Product features

- 3 operating modes selectable (light continous on, switch-on by movement or dusk)
- Zero crossing circuit optimized for LED luminaire operation
- Type of protection: IP55



- Protection class: II

#### **TECHNICAL DATA**

# Electrical data

Nominal voltage	220240 V
Mains frequency	5060 Hz
Protection class	П

# **Dimensions & Weight**

Length	76.00 mm
Width	95.00 mm
Height	111.00 mm
Product weight	214.00 g



### Materials & Colors

Product color	Dark grey
Body material	Polycarbonate (PC)
Mercury content	0.0 mg

# Application & Mounting

Ambient temperature range	-20+40 °C
Temperature range at storage	-25+70 °C
Type of connection	Screw terminal, 3-Pole
Type of protection	IP55
Dimmable	No
Mounting type	Surface
Mounting location	Wall
Replaceable light source	No

#### Lifespan

Lifespan L70/B50 at 25 °C 50	0000 h <sup>1)</sup>
------------------------------	----------------------

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

#### Sensor

Type of sensor	Light / Motion
Sensor technology	Passive infrared (PIR)
Sensor detection angle	360 °
Sensor controlled switching time	2 s15 min
Detection range of motion sensor	10 m
Detection threshold of daylight sensor	11000 lx

## Certificates & Standards

Standards CE / EAC / UKCA	Standards	CE / EAC / UKCA
---------------------------	-----------	-----------------

#### Safety advice

- All electrical connections must be made by a qualified person.

- Caution, risk of electric shock.

- Check wall-ceiling for suitability. If uncertain, seek professional advice.

# DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	User instruction / safety instructions	SENSOR WALL 360DEG	
PDF	Declarations of conformity	SENSOR WALL 360DEG	

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075244832	Folding box 1	82 mm x 118 mm x 116 mm	249.00 g	1.12 dm <sup>3</sup>
4058075244849	Shipping box 8	250 mm x 178 mm x 248 mm	2203.00 g	11.04 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.