

PRODUCT DATASHEET WALL SCONCE CCT SELECT 14W

SYLVANIA Wall Sconce CCT Selectable | SYLVANIA Wall Sconce luminaire with selectable CCT



Areas of application

- Indoor applications
- Bathrooms
- Entryways & foyers
- Hallways
- Corridors

Product features

- Selectable CCTs: 2700/3000/3500/4000/5000K
- Input Voltage: 120Vac
- No warm up time, instant on with full light and consistent lamp to lamp color
- Uniform, glare free illumination distribution
- Easy installation no additional hardware needed
- Lifetime (L70): up to 50,000 h

TECHNICAL DATA

Electrical data

Nominal wattage	14.00 W
Nominal voltage	120277 V

Photometrical data

Luminous flux	1150 lm
Luminous efficacy	82 lm/W
Color temperature	2700 5000 K
Color rendering index Ra	90

Dimensions & Weight

Length	235.00 mm
Width	100.00 mm
Height	267.00 mm
Product weight	776.00 g

Materials & Colors

Product color	White
Housing color	White
Body material	Polycarbonate (PC)

Application & Mounting

Dimmable	No	
Mounting type	Surface	
Replaceable light source	No	

Certificates & Standards

Replaceable light source (EPREL) Not replaceable

Additional product data

NAED 65570

EQUIPMENT / ACCESSORIES

- Mounting screws and mounting brackets included

Safety advice

- cETLus, RoHS, FCC
- For indoor use only; not suitable for outdoor or wet locations

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

DOWNLOAD DATA

	Spec Sheets and Product Docume	ents Document name	
POF	Extended installation guide	WALL SCONCE MANUAL	
POF	Product information bulletin	Hi-PerformanceLED™ Selectable Wall Sconce	
	Dhatamatria and limbing decim		
	Photometric and lighting design files	Document name	
	IES file (IES)	WALL SCONCE, 9 INCH, 14W, 1150LM, 120- 277V, CRI 90, 5 CCT SELECTABLE IES FILES	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135655708	Folding box 1	242 mm x 277 mm x 108 mm	965.00 g	7.24 dm ³
10046135655705	Shipping box	443 mm x 257 mm x 295 mm	4298.00 g	33.59 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.