

PRODUCT DATASHEET

POLE S R A 25 5IN D4 BL

POLES STRAIGHT ROUND ALUMINUM | LEDVANCE Round Aluminum Poles



Areas of application

- Parking lots
- Parks
- Pedestrian walkways
- Outdoor storage areas
- Small sports lighting
- Outdoor open spaces

Product features

- Poles available in 3 heights: 12', 20', and 25'
- 12'-20' are 4" diameter; 20' and 25' are 5" diameter
- Poles have a uniform wall thickness of 0.196" (5mm)
- Fabricated from 6063 Aluminum Alloy with T6 Temper
- Die cast anchor base from 356 Aluminum Alloy
- Reinforced 3" x 5" die cast aluminum hand hole with cover and ground screw
- Drilled poles include UV-stabilized polycarbonate spring loaded top cover
- Available in black finish

TECHNICAL DATA

Dimensions & Weight

Product weight	50802.3 g
----------------	-----------

Application & Mounting

Replaceable light source	No
--------------------------	----

Additional product data

NAED	66026
------	-------

Accessories Optional

Product image	Product name	EAN
	POLES R 2A ADAPT TENON 4IN BZ	0046135662126
	POLES R 2A ADAPT TENON 4IN BL	0046135662133
	POLES R 2A ADAPT TENON 4IN GR	0046135662140

EQUIPMENT / ACCESSORIES

- Anchor bolts
- Easily secured 2-piece base cover
- Bolt circle template

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854279140	Shipping box 1	7,645 mm x 119 mm x 119 mm	62282.00 g	108.41 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.