

PRODUCT DATASHEET DOOR KIT LINK 2x2 EMBB UNH

DOOR KIT LINK™ | Door Kit luminaire featuring built-in LEDVANCE LINK bluetooth low energy mesh connectivity

Areas of application

- Offices
- Retail
- Hallways
- Multipurpose Rooms
- Hospitality

Product features

- Selectable CCT: 3000/3500/4000/5000K
- Bluetooth® Low Energy Mesh and a range of up to 100 ft between luminaires
- Easy to deploy install, commission, and control
- Convenient control via LINK™ app or wireless wall/controller
- Optional LINK PIR sensor enables field-installable occupancy & daylight control
- DLC listing maximizes rebate opportunities
- Up to 125 LPW
- Optional emergency battery backup versions
- CRI > 80
- Wirelessly sync luminaires and set group/individual scenes using the LINK app

TECHNICAL DATA

Electrical data

| Nominal wattage | 30.00 W |
|-----------------|----------|
| Nominal voltage | 120347 V |

Photometrical data

| Luminous flux | 1905 3810 lm |
|--------------------------|--------------|
| Luminous efficacy | 127 lm/W |
| Color temperature | 3000 5000 K |
| Color rendering index Ra | > 80 |

Dimensions & Weight

| Length | 605.00 mm |
|----------------|-----------|
| Width | 606.00 mm |
| Height | 78.50 mm |
| Product weight | 3330.00 g |

Materials & Colors

| Product color | White |
|-----------------|--------|
| Housing color | White |
| Body material | Steel |
| Mercury content | 0.0 mg |

Application & Mounting

| Dimmable | Yes |
|--------------------------|----------|
| Type of dimming | 0-10V |
| Mounting type | Recessed |
| Application environment | Indoor |
| Replaceable light source | No |

BATTERY

Certificates & Standards

| Replaceable light source (EPREL) | Not replaceable |
|----------------------------------|-----------------|
|----------------------------------|-----------------|

Additional product data

| NAED | 64285 |
|------|-------|
| | |

Accessories Optional

| Product image | Product name | EAN | |
|---------------|---|----------------|--|
| 4 | AREA DUSK-TO-DAWN 55W 120-277V D 3CCT T5 GR P | 10046135617512 | |

EQUIPMENT / ACCESSORIES

- Mounting brackets

Safety advice

- Retrofit luminaire is designed to be installed in existing troffers

DOWNLOAD DATA

| Photometric and lighting design files | Document name | |
|---------------------------------------|---|--|
| IES file (IES) | IES files for DUAL SELECTABLE RETROFIT DOOR KIT GENERATION 7B | |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854609060 | Unpacked 2 | 605 mm x 606 mm x 79 mm | 6660.00 g | 28.78 dm ³ |
| 4099854311116 | Shipping box 2 | 648 mm x 632 mm x 132 mm | 7599.00 g | 54.06 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.