

PRODUCT DATASHEET

LEDMD SLIM SELECT 2A 6" 5CCT 1200LM 120V 4PK

SYLVANIA MICRODISK SLIM CCT SELECTABLE | Slim Microdisk Downlight with selectable 5 CCT

Areas of application

- Residential
- New installations or retrofit of existing installations



Product features

- Canless recessed flush mount downlight with remote driver design for easy installation
- 1/2" height allows installation directly under joists
- Selectable CCTs: 2700/3000/3500/4000/5000K
- Flicker-free dimming, Phase-cut
- Up to 80 LPW
- Energy savings up to 92 %
- Available in 120VAC
- Beam Angle of 112° FWHM
- 90 CRI, R9>50

TECHNICAL DATA

Electrical data

Nominal wattage	16.00 W
Nominal voltage	120 V

Photometrical data

Luminous flux	1200 lm
Luminous efficacy	75 lm/W
Color temperature	2700 ... 5000 K
Color rendering index Ra	90

Dimensions & Weight

Diameter	172.72 mm
Height	22.86 mm
Product weight	302.00 g

Materials & Colors

Product color	White
Housing color	White
Body material	Plastic

Application & Mounting

Dimmable	Yes
Type of dimming	PHASE CUT
Mounting type	Recessed
Replaceable light source	No

Certificates & Standards



Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

Additional product data

NAED	61406
------	-------

Accessories Optional

Product image	Product name	EAN
	MD EXT CABLE 6FT WH	0046135608988
	MD EXT CABLE 10FT WH	0046135608995
	MD EXT CABLE 20FT WH	0046135609008

Product image	Product name	EAN
	SLIM MD FRAME	0046135629594
	MD FRAME T-GRID	0046135637438


EQUIPMENT / ACCESSORIES

- Luminaire with interconnected cable to galvanized steel remote driver wiring enclosure via FT6 cable
- 3 Push-on Wire Terminals

Safety advice

- Suitable for indoor, dry, and wet locations.
- IC Rated.
- Not intended for use with emergency light luminaires or exit lights.
- Suitable for use in closets, compliant with NFPA 70, NEC section 410.16 (A)(3) and 410.16 (C)(5).
- For use in housings that can structurally support a lamp weighing one pound.
- Max Ceiling Thickness 0.37" (9.4 mm).

DOWNLOAD DATA

Documents and certificates	Document name
 Product information bulletin	ValueLED Selectable Slim MICRODISK

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135614064	Folding box 4	181 mm x 187 mm x 181 mm	1466.00 g	6.14 dm ³
10046135614061	Shipping box 16	387 mm x 192 mm x 192 mm	6265.00 g	14.29 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.