

# PRODUCT DATASHEET

## LED NFC PROGRAMMABLE DRIVER 2CH 85W UNH DIM AUX

tapTronic™ NFC LED Driver Constant Current 2-Channel Output | NFC Programmable LED driver with 2 channel output



---

### Areas of application

- Wall and ceiling
- Recessed and surface-mounted ceiling luminaires
- Suspended luminaires

---

### Product features

- Field-programmable via free app
- Dim to off – dim range 1-100 %
- Constant lumen output
- Soft start
- End of life
- Thermal protection
- DC Auxiliary output
- cULus Class 2 and Class P
- The two-channel outputs are independent of each other without interference
- App is multi-lingual: English/French/Spanish/Portuguese

TECHNICAL DATA

Electrical data

|                 |             |
|-----------------|-------------|
| Nominal wattage | 85.00 W     |
| Nominal voltage | 120...347 V |
| Mains frequency | 50...60 Hz  |

Dimensions & Weight

|                |           |
|----------------|-----------|
| Length         | 380.00 mm |
| Width          | 31.00 mm  |
| Height         | 26.00 mm  |
| Product weight | 250.00 g  |

Additional product data

|      |       |
|------|-------|
| NAED | 75892 |
|------|-------|

Capabilities

|          |     |
|----------|-----|
| Dimmable | Yes |
|----------|-----|

Certificates & Standards

|                    |      |
|--------------------|------|
| Protection class   | II   |
| Type of protection | IP20 |

Safety advice

- Always power off the driver before making any changes in programming via app.

DOWNLOAD DATA

| Spec Sheets and Product Documents                                                  |                              | Document name                                                                                     |
|------------------------------------------------------------------------------------|------------------------------|---------------------------------------------------------------------------------------------------|
|  | Extended installation guide  | tapTronic 55W 2-Independent Channels                                                              |
|  | Product information bulletin | ECS315 LEDVANCE TapTronic NFC LED Drivers NFC Programmable Constant Current 2-Channel LED Drivers |

LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume   |
|---------------|------------------------------|--------------------------------------|--------------|----------|
| 0046135758928 | Unpacked<br>1                | 380 mm x 31 mm x 26 mm               | 250.00 g     | 0.31 dm³ |

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume    |
|---------------|------------------------------|--------------------------------------|--------------|-----------|
| 4099854308161 | Shipping box<br>20           | 400 mm x 195 mm x 190 mm             | 5315.00 g    | 14.82 dm³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.