

PRODUCT DATASHEET

LED NCF PROGRAMMABLE DRIVER LINEAR

36W UNV 1000mA DIM1 AUX12

tapTronic™ NFC LED Driver Constant Current Linear | Linear NFC Programmable LED driver

Areas of application

- Wall and ceiling
- Recessed and surface-mounted ceiling luminaires
- Suspended luminaires



Product features

- Field-programmable via free app
- Dim to off – dim range 1-100 %
- Constant lumen output
- Soft start
- End of life
- Thermal protection
- DC Auxiliary output
- cULus Class 2 and Class P
- App is multi-lingual: English/French/Spanish/Portuguese

TECHNICAL DATA

Electrical data

Nominal wattage	36.00 W
Nominal voltage	120...277 V
Mains frequency	50...60 Hz

Dimensions & Weight

Length	241.30 mm
Width	31.10 mm
Height	28.00 mm
Product weight	550.00 g

Capabilities

Dimmable	Yes
----------	-----





Certificates & Standards

Protection class	I
Type of protection	IP20

Safety advice

- Suitable for dry and damp environments.

DOWNLOAD DATA

Documents and certificates		Document name
	Extended installation guide	Installation Guide-tapTronic Linear
	Product information bulletin	NFC LED Drivers
	Product information bulletin	NFC LED Drivers
	Product information bulletin	NFC LED Drivers

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854010668	Unpacked 1			

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075794313	Shipping box 24	330 mm x 260 mm x 195 mm	13555.00 g	16.73 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.