

# PRODUCT DATASHEET

## LED NCF PROGRAMMABLE DRIVER LINEAR

### 85W UNH 2300mA DIM1 AUX

tapTronic™ NFC LED Driver Constant Current Linear | Linear NFC Programmable LED driver

---

#### Areas of application

- Wall and ceiling
- Recessed and surface-mounted ceiling luminaires
- Suspended luminaires



---

#### Product features

- Field-programmable via free app
- Dim to off – dim range 1-100 %
- Constant lumen output
- Soft start
- End of life
- Thermal protection
- DC Auxiliary output
- cULus Class 2 and Class P
- App is multi-lingual: English/French/Spanish/Portuguese

## TECHNICAL DATA

### Electrical data

Nominal wattage	85.00 W
Nominal voltage	120...347 V
Mains frequency	50...60 Hz

### Dimensions & Weight

Length	280.00 mm
Width	30.00 mm
Height	21.00 mm
Product weight	280.00 g

### Additional product data

NAED	75898
------	-------


### Capabilities

Dimmable	Yes
----------	-----

### Safety advice

- Suitable for dry and damp environments.

## DOWNLOAD DATA

Documents and certificates		Document name
	Extended installation guide	Installation guide tapTronic 55W 85W 2-Independent Channels NFC Linear

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135758980	Unpacked 1	380 mm x 30 mm x 25 mm	280.00 g	0.29 dm <sup>3</sup>
4099854373114	Shipping box 20	400 mm x 195 mm x 190 mm	5915.00 g	14.82 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

