

PRODUCT DATASHEET

LED NCF PROGRAMMABLE DRIVER

OUTDOOR 100W HUV 1250mA DIM AUX12

IP65

tapTronic™ NFC LED Driver Constant Current Outdoor | Outdoor NFC programmable LED driver



Areas of application

- Area lights
- Industrial high bays
- Wall packs
- Décor landscape
- Cobraheads
- Bollards
- Hazardous locations

Product features

- Field-programmable via free app
- Dim to off – dim range 10-100 %
- Constant lumen output
- Soft start
- End of life
- Thermal protection
- DC Auxiliary output
- cULus Class P
- IP65
- App is multi-lingual: English/French/Spanish/Portuguese

TECHNICAL DATA

Electrical data

Nominal wattage	100.00 W
Nominal voltage	347...480 V
Mains frequency	50...60 Hz

Dimensions & Weight

Length	240.50 mm
Width	59.90 mm
Height	38.10 mm
Product weight	1000.00 g

Additional product data

NAED	75887
------	-------


Capabilities

Dimmable	Yes
----------	-----

Certificates & Standards

Type of protection	IP66
--------------------	------

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	Extended installation guide	installation guide 100W NFC Outdoor Constant Current LED Driver

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854298974	Unpacked 1	241 mm x 60 mm x 38 mm	1000.00 g	0.55 dm³
4099854237638	Shipping box 10	463 mm x 285 mm x 144 mm	10459.00 g	19.00 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.