

PRODUCT DATASHEET

OT 50W UNV 1250C 2DIM LT2 P6

OPTOTRONIC® CONSTANT CURRENT OUTDOOR - OUTDOOR PROGRAMMABLE LED POWER SUPPLIES - 0-10V DIM - IP66 | OPTOTRONIC® Constant Current Outdoor – Programmable LED Power Supplies (0-10V Dim, IP66)



Product features

- OEM programmable with 1mA resolution to match LED load and maximize performance
- Dimming down to 1 % on 0-10V dimmers
- AstroDIM, LEDset, constant lumen maintenance, LED thermal protection, AUX output
- Programming does not require powering up or connecting to AC line voltage
- High levels of line transient protection for outdoor applications (6kV, 4kV EFT)
- IP66
- UL Class P Listed

TECHNICAL DATA

Electrical data

Nominal wattage	65.00 W
Nominal voltage	120...277 V
Mains frequency	50...60 Hz

Dimensions & Weight

Length	168.00 mm
Width	43.50 mm
Height	30.00 mm
Product weight	380.00 g

Additional product data

NAED	79371
------	-------

Capabilities

Dimmable	No
----------	----

Certificates & Standards

Protection class	II
Type of protection	IP66

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	Product information bulletin	OPTOTRONIC Programmable Outdoor Constant Current Dimmable LED Power Supplies

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899158474	Unpacked 1		380.00 g	
4052899156692	Shipping box 20	287 mm x 185 mm x 160 mm	7963.00 g	8.51 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.