

PRODUCT DATASHEET ULTRA LED A19 9W DIM FR 3500K 1PK

SYLVANIA ULTRA A19 Lamps | Dimmable ULTRA A19 LED lamps with 80+ CRI and 15,000-hour rated life



Areas of application

- Downlights, pendant fixtures, table lamps, wall sconces
- Healthcare, hospitality, residential, retail
- Indoor and outdoor
- Suitable for rough service

Product features

- 15,000 hours lifetime (L70)
- RoHS compliant, mercury and lead free
- UV and IR free
- Reduces energy consumption up to 85 %
- Last up to 20 times longer than incandescent lamps
- No warm-up time, instant-on with full light output and stable color
- Dimmable down to 10 %
- Approved for enclosed fixtures

TECHNICAL DATA

Electrical data

Nominal wattage	9 W
Construction wattage	9.00 W
Nominal voltage	120 V
Claimed equiv. conventional lamp power	60 W

Photometrical data

Luminous flux	800 lm
Luminous efficacy	88 lm/W
Color temperature	3500 K
Color rendering index Ra	80
Light color	835

Dimensions & Weight

Overall length	107.54 mm
Diameter	59.99 mm
Product weight	53.00 g

Additional product data

Base (standard designation)	E26
Mercury content	0.0 mg
NAED	71185

Capabilities

Country-specific categorizations

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E26
Length	107.54 mm
Height	59.99 mm
Width	59.99 mm

Safety advice

- Suitable for damp locations.
- Not for use with emergency light fixtures or exit lights.
- -4°F and + 113°F (-20°C and +45°C)

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	Product information bulletin	ULTRA LED A-line Lamps

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135711855	Folding box 1	64 mm x 95 mm x 140 mm	108.00 g	0.84 dm ³
10046135711852	Shipping box 6	279 mm x 260 mm x 187 mm	826.00 g	13.63 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.