

# PRODUCT DATASHEET

## Contractor Series 10YR A19 6W FR 2700K 2PK

SYLVANIA Contractor Series A19 Lamps | SYLVANIA Contractor Series are rated for up to 11,000 hours



---

### Areas of application

- Downlights, pendant fixtures, table lamps, wall sconces
- Healthcare, hospitality, residential, retail
- Suitable for rough service

---

### Product features

- Reduces energy consumption up to 86 %
- 11,000 hours lifetime (L70)



- No warm-up time, instant-on with full light output and stable color

## TECHNICAL DATA

### Electrical data

Nominal wattage	6 W
Construction wattage	6.00 W
Nominal voltage	120 V
Claimed equiv. conventional lamp power	40 W
Operating frequency	50...60 Hz
Mains frequency	50...60 Hz

### Photometrical data

Luminous flux	450 lm
Luminous efficacy	75 lm/W
Color temperature	2700 K
Color rendering index Ra	80
Light color	827

### Dimensions & Weight

Overall length	111.99 mm
Diameter	59.94 mm
Product weight	50.00 g

### Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

### Additional product data

Base (standard designation)	E26
Mercury content	0.0 mg
Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
NAED	74077

### Capabilities

Dimmable	No
----------	----

## Certificates &amp; Standards

Standards	RoHS / CSA / FTC / FCC / cETLus
-----------	---------------------------------

## Country-specific categorizations

Order reference	6W/827 120V 6X2
-----------------	-----------------


## Energy labelling regulation data acc EU 2019/2015


Light source cap-type (or other electric interface)	E26
Length	111.99 mm
Height	59.94 mm
Width	59.94 mm

## Safety advice

- Suitable for damp locations.
- Non-dimmable.
- -4°F and +104°F (-20°C and +40°C)
- Approved for use in totally enclosed fixtures.

## DOWNLOAD DATA

Documents and certificates	Document name
 Product information bulletin	Contractor Series LED A19 Lamps

Photometric and lighting design files	Document name
 IES file (IES)	LED A19, 6W 80CRI, 450 Lumen 2700K IES FILE

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135740770	Folding box 2	60 mm x 108 mm x 114 mm	132.00 g	0.74 dm <sup>3</sup>
10046135740777	Shipping box 12	337 mm x 133 mm x 130 mm	927.00 g	5.84 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.