

# PRODUCT DATASHEET Contractor Series 10YR A19 8.5W FR 3000K 1PK

SYLVANIA Contractor Series A19 Lamps | SYLVANIA Contractor Series are rated for up to 11,000 hours



### Areas of application

- Downlights, pendant fixtures, table lamps, wall sconces
- Healthcare, hospitality, residential, retail
- Suitable for rough service

### Product features

- Reduces energy consumption up to 86 %
- 11,000 hours lifetime (L70)



- No warm-up time, instant-on with full light output and stable color

# **TECHNICAL DATA**

# Electrical data

Nominal wattage	8.5 W	
Construction wattage	8.50 W	
Nominal voltage	120 V	
Claimed equiv. conventional lamp power	60 W	
Operating frequency	5060 Hz	
Mains frequency	5060 Hz	

### Photometrical data

Luminous flux	800 lm
Luminous efficacy	94 lm/W
Color temperature	3000 K
Color rendering index Ra	80
Light color	830

# Dimensions & Weight

Overall length	110.01 mm
Diameter	60.00 mm
Product weight	50.00 g

# Temperatures & operating conditions

Ambient temperature range	-20+45 °C
---------------------------	-----------

# Additional product data

Base (standard designation)	E26	
Mercury content	0.0 mg	
Mercury-free	Yes	
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	

# Capabilities

Dimmable	No
----------	----

# Certificates & Standards

Standards	RoHS / FTC / FCC / CSA / cETLus	
Country-specific categorizations		
Order reference	8,5W/830 120V 6	
Energy labelling regulation data acc EU 2019/2015		
Energy labelling regulation data acc EU 2019/2015  Light source cap-type (or other electric interface)	E26	
Light source cap-type (or other electric interface)	E26 110.01 mm	
Energy labelling regulation data acc EU 2019/2015  Light source cap-type (or other electric interface)  Length  Height		

# Safety advice

- Suitable for damp locations.
- Non-dimmable.
- -4°F and +104°F (-20°C and +40°C)
- Approved for use in totally enclosed fixtures.

### **DOWNLOAD DATA**

	Documents and certificates	Document name	
PDF	Product information bulletin	Contractor Series LED A19 Lamps	
	Photometric and lighting design files	Document name	
	IES file (IES)	LED A19, 8.5W 80CRI, 800 Lumen, 3000K IES FILE	

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135747335	Folding box 1	60 mm x 60 mm x 114 mm	77.00 g	0.42 dm <sup>3</sup>
10046135747332	Shipping box 6	206 mm x 137 mm x 124 mm	581.00 g	3.49 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.