

# PRODUCT DATASHEET

## High Output Reflector R20 7W DIM HO 2700K 1PK

SYLVANIA High Output Reflectors | High Lumen Package LED Reflectors



---

### Areas of application

- Downlights, pendant fixtures, table lamps, wall sconces
- Healthcare, hospitality, residential, retail
- General lighting, recessed downlights, track lighting, wall washers
- Art galleries, museums, offices, restaurants

---

### Product features

- Long life up to 25,000 hours (L70)
- CRI of 80 ensures good color definition
- UV and IR free
- RoHS compliant, mercury and lead free
- Energy savings up to 90 %
- Dimmable down to 10 %

## TECHNICAL DATA

### Electrical data

Nominal wattage	6 W
Construction wattage	6.00 W
Nominal voltage	120 V
Claimed equiv. conventional lamp power	50 W

### Photometrical data

Luminous flux	525 lm
Luminous efficacy	87 lm/W
Color temperature	2700 K
Color rendering index Ra	80
Light color	827

### Dimensions & Weight

Overall length	95.00 mm
Diameter	63.00 mm
Product weight	150.00 g

### Additional product data

Base (standard designation)	E26
Mercury content	0.0 mg
NAED	40462

### Capabilities

Dimmable	Yes
----------	-----

### Country-specific categorizations

Order reference	7W/827 120V 6X1
-----------------	-----------------

### Energy labelling regulation data acc EU 2019/2015


Light source cap-type (or other electric interface)	E26
Correlated colour temperature type	SINGLE_VALUE
Length	95.00 mm
Height	63.00 mm
Width	63.00 mm

### Safety advice

- Suitable for damp locations – not for use where directly exposed to water.
- -4°F to +104°F (-20°C to +40°C)

- Not for use with emergency light fixtures or exit lights.
- Not for use in totally enclosed fixtures.

DOWNLOAD DATA

Documents and certificates		Document name
	Product information bulletin	ULTRA LED HO Reflector Lamps

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135404627	Folding box 1	70 mm x 89 mm x 140 mm	214.00 g	0.87 dm³
10046135404624	Shipping box 6	235 mm x 206 mm x 149 mm	1462.00 g	7.24 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.