

PRODUCT DATASHEET LED TruWave® PAR Lamps PAR30 10.5W DIM 3000K NFL 25 1PK

SYLVANIA TruWave® PAR Lamps | PAR Lamps with exceptional quality lighting with high CRI and reduce blue wavelengths



Areas of application

- Downlights, pendant fixtures, table lamps, wall sconces
- Healthcare, hospitality, residential, retail

Product features

- Controls blue wavelengths for lower glare and reduced eye strain to improve readability
- Clean light color rendering for seeing realistic, vivid colors
- Exceptional color quality without the loss of efficacy typical of most 90+ CRI solutions
- Properly saturates red to make building spaces and flesh tones accurate and vibrant
- Up to 85 LPW
- 25,000 hours lifetime (L70)
- 5-year limited warranty
- Dimmable down to 10 %

TECHNICAL DATA

Electrical data

Nominal wattage	10 W
Construction wattage	10.00 W
Nominal voltage	120 V
Claimed equiv. conventional lamp power	75 W

Photometrical data

Luminous flux	850 lm
Luminous efficacy	85 lm/W
Color temperature	3000 K
Color rendering index Ra	90
Light color	930

Dimensions & Weight

Overall length	114.00 mm
Diameter	95.00 mm
Product weight	210.00 g

Additional product data

Base (standard designation)	E26
Mercury content	0.0 mg

Capabilities

Dimmable Yes

Country-specific categorizations

Order reference CL 10,5W/930 12

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E26
Length	114.00 mm
Height	95.00 mm
Width	95.00 mm

Safety advice

- Not for use in totally enclosed fixtures.
- Suitable for indoor and outdoor dry, damp and wet locations.
- -4°F to +113°F (-20°C to +45°C)
- Not for use with emergency light fixtures or exit lights.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	Product information bulletin	Natural Series PAR Family

Photometric and lighting design files	Document name
IES files (IES, additional)	LED10.5PAR30LNDIM930TL

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135409103	Folding box 1	98 mm x 98 mm x 156 mm	283.00 g	1.51 dm ³
10046135409100	Shipping box 6	315 mm x 216 mm x 166 mm	1979.00 g	11.29 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.