

PRODUCT DATASHEET

ULTRA LED™ HO PAR Lamps PAR38 23W HO DIM 3000K FL 40 1PK

SYLVANIA High Output PAR Lamps | High lumen package LED PAR lamps



Areas of application

- Downlights, pendant fixtures, table lamps, wall sconces
- Healthcare, hospitality, residential, retail
- Grocery
- Houses of worship

Product features

- High CBCP performance
- Up to 100 LPW
- Outstanding color uniformity and beam quality utilizing COB technology
- 277V option allows compatible replacement for HID lamps
- UL1993 & UL1598C tested
- Great replacement options for high power halogen and HID lamp
- 25,000 hours lifetime (L70)
- Dimmable down to 10 %

TECHNICAL DATA

Electrical data

Nominal wattage	23 W
Construction wattage	23.00 W
Nominal voltage	120 V
Claimed equiv. conventional lamp power	250 W

Photometrical data

Luminous flux	2650 lm
Luminous efficacy	115 lm/W
Color temperature	3000 K
Color rendering index Ra	80
Light color	830

Dimensions & Weight

Overall length	134.00 mm
Diameter	134.00 mm
Product weight	440.00 g

Additional product data

Base (standard designation)	E26
Mercury content	0.0 mg
NAED	42343

Capabilities

Dimmable	Yes
----------	-----

Country-specific categorizations

Order reference	WHITE 23W/830 1
-----------------	-----------------

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E26
Length	134.00 mm
Height	134.00 mm
Width	134.00 mm

Safety advice

- Use in fixtures that support a half-pound lamp.
- -4°F to +104°F (-20°C to +40°C)
- Not for use with emergency light fixtures or exit lights.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135423437	Folding box 1	133 mm x 133 mm x 153 mm	530.00 g	2.71 dm³
4058118305643	Shipping box 6	415 mm x 281 mm x 172 mm	3488.00 g	20.06 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.