

PRODUCT DATASHEET

ULTRA LED™ Glass PAR Lamps 11W PAR30 DIM 3000K FL 40 1PK

SYLVANIA ULTRA LED™ PAR Lamps | ULTRA LED PAR Lamps



Areas of application

- Downlights, pendant fixtures, table lamps, wall sconces
- Healthcare, hospitality, residential, retail

Product features

- Longer life than traditional halogen lamps
- Glass body with full optics – similar to halogen PAR lamps
- CRI of 80 ensures good color definition
- RoHS compliant, mercury and lead free
- Dimmable down to 10 %
- Wet rated

TECHNICAL DATA

Electrical data

Nominal wattage	11 W
Construction wattage	11.00 W
Nominal voltage	120 V
Claimed equiv. conventional lamp power	75 W

Photometrical data

Luminous flux	850 lm
Luminous efficacy	77 lm/W
Color temperature	3000 K
Color rendering index Ra	82
Light color	830

Dimensions & Weight

Overall length	84.99 mm
Diameter	95.00 mm
Product weight	190.00 g

Additional product data

Base (standard designation)	E26
-----------------------------	-----

Capabilities

Dimmable	Yes
----------	-----

Country-specific categorizations

Order reference	11W/830 120V 6X
-----------------	-----------------

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E26
Length	84.99 mm
Height	95.00 mm
Width	95.00 mm

Safety advice

- Suitable for wet locations.
- -4°F to +113°F (-20°C to +45°C)
- Not for use with emergency light fixtures or exit lights.
- Approved for use in enclosed fixtures.

DOWNLOAD DATA

Documents and certificates		Document name
	Product information bulletin	ULTRA LED Glass PAR Lamps

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135410499	Folding box 1	102 mm x 114 mm x 146 mm	281.00 g	1.70 dm³
4058118192755	Shipping box 6	316 mm x 238 mm x 162 mm	1925.00 g	12.18 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.