

PRODUCT DATASHEET

Contractor Series 5CCT Selectable LED PAR Lamps PAR38 15W 10YV FL 40 1PK

SYLVANIA Contractor Series 5CCT Selectable PAR Lamps | PAR Lamps rated up to 11,000 hours life with 5 CCT selectable options



Areas of application

- Downlights, pendant fixtures, table lamps, wall sconces
- Healthcare, hospitality, residential, retail

Product features

- Selectable CCTs: 2700/3000/3500/4000/5000K
- Dimmable down to 10 %
- Controls blue wavelengths for lower glare and reduced eye strain to improve readability
- 25,000 hours lifetime (L70)
- Supports an improved sleep-wake cycle
- Clean light color rendering for seeing realistic, vivid colors
- Twist the toggle located towards the base of the lamp to easily change between CCTs
- 5-year limited warranty

TECHNICAL DATA

Electrical data

Nominal wattage	15 W
Construction wattage	15.00 W
Nominal voltage	120 V
Claimed equiv. conventional lamp power	150 W

Photometrical data

Luminous flux	1600 lm
Luminous efficacy	106 lm/W
Color temperature	2700 K
Color rendering index Ra	80
Light color	827

Dimensions & Weight

Overall length	130.00 mm
Diameter	120.00 mm
Product weight	115.00 g

Additional product data

Base (standard designation)	E26
Mercury content	0.0 mg
NAED	42573

Capabilities

Dimmable	Yes
----------	-----

Country-specific categorizations

Order reference	15W 120V 4X1 EN
-----------------	-----------------

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E26
Length	130.00 mm
Height	120.00 mm
Width	120.00 mm

Safety advice

- Suitable for indoor dry, damp and wet locations.
- -4°F to +113°F (-20°C to +45°C)

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	Product information bulletin	LED620 SYLVANIA LAMPS Contractor Series 5CCT Selectable LED family

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135425738	Folding box 1	120 mm x 120 mm x 134 mm	161.00 g	1.93 dm³
4058118318025	Shipping box 4	507 mm x 136 mm x 145 mm	870.00 g	10.00 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.