

PRODUCT DATASHEET F T5 13W CW BL 16

SYLVANIA Preheat T5 | Miniature preheat T5 lamps for magnetic ballast systems with starter use



Product features

- 6 inch lamps available in Cool White phosphor
- 9 inch lamps available in Cool White phosphor
- 12 inch lamps available in Soft (Warm) White and Cool White phosphor
- 21 inch lamps available in Soft (Warm) White and Cool White phosphor



TECHNICAL DATA

Electrical data

Nominal wattage	13 W	
Construction wattage	13.00 W	
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body	

Photometrical data

Luminous flux	830 lm	
Luminous efficacy	63 lm/W	
Color temperature	4200 K	
Color rendering index Ra	60	
Light color	642	
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body	

Dimensions & Weight

Overall length	531.09 mm
Diameter	16.00 mm
Tube diameter	16 mm
Product weight	45.00 g

Lifespan

Service life	4500 h
--------------	--------

Additional product data

Base (standard designation)	G5
Mercury content	21.5 mg
Design / version	Basic T5 short tubular, G5 base
NAED	21315

Capabilities

Dimmable	No
----------	----

Country-specific categorizations

Order reference	F13T5CWBL16 6/C

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G5

Length	533.40 mm
Height	16.00 mm
Width	16.00 mm

Safety advice

- Starter required for operation.
- Operate on magnetic ballasts.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135213151	BAG 1	600 mm x 73 mm x 18 mm	66.00 g	0.79 dm ³
10046135213158	Shipping box	114 mm x 58 mm x 614 mm	551.00 g	4.06 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.