

PRODUCT DATASHEET

LEDVANCE HE BALLAST 2X39W T5 HO UNV PS N

T5 FLUORESCENT BALLASTS 120-277V | T5/T5HO programmed rapid start ballasts with low THD and universal 120-277V input



Product features

- High-efficiency operation with energy savings and long system life
- Universal 120–277V input for flexible applications
- Low THD and high power factor
- Compatible with ANSI-standard fluorescent lamp equivalents
- Backed by a five-year limited warranty

TECHNICAL DATA

Electrical data

Nominal voltage	120...277 V
Mains frequency	50...60 Hz

Dimensions & Weight

Length	241.30 mm
Width	33.02 mm
Height	25.40 mm
Product weight	363.00 g



Additional product data

NAED	75895
------	-------

Capabilities

Dimmable	No
----------	----

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	Certificates	LEDVANCE Ballast Limited Warranty
	Product information bulletin	LEDVANCE T5HO & T5 Programmed Rapid Start ECS310

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
0046135758959	Unpacked 1	241 mm x 33 mm x 25 mm	363.00 g	0.20 dm ³
4099854322440	Shipping box 10	276 mm x 251 mm x 74 mm	3888.00 g	5.13 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.