

PRODUKTDATABLAD DALI ACU BT

DALI ACU BT | Kontrollenheter for lysstyringssystemer



Bruksområder

- Offices
- Conference rooms
- Training rooms
- Classrooms
- Corridors
- Shop lighting

Produktfordeler

- Control the light via Smartphone
- Adjustment of all settings via smartphone
- Plug and Play: Basic features usable without App
- Simplified startup thanks to predefined operation modes
- Intuitive manual dimming, switching and changing of colour temperature
- Up to 4 groups separately controllable
- Adjustable Offset for different groups
- Easy Scene creation via App
- Scene-recall via OSRAM DALI PRO PB coupler possible
- Firmware update over-the-air via Bluetooth possible
- Integrated DALI supply
- Control of standard white or Tunable White light acc. DALI device type 8 (DT8)*
- Selected DALI parameters changeable via APP

Produktfunksjoner

- Compact light control with DALI interface
- Smart phone connection via Bluetooth to control and configure
- One DALI output channel (Broadcast or Groupcast)
- Up to 32 DALI luminaires connectable
- Supports up to 4 OSRAM DALI sensors and pushbutton couplers


- Daylight-dependent regulation and presence-dependent control of light
- Separate pushbutton input to operate via standard pushbutton
- Supports DALI DT8 Tunable White driver
- Outputs with electronical reversible overtemperature, short-circuit, overload protection
- Length of the DALI control cable: up to 300 m
- Length of the pushbutton cable: up to 50 m
- Suitable for flush box mounting

TEKNISKE DATA

ELEKTRISK INFORMASJON

Nominell effekt	3,00 W
Nominell spenning	220...240 V
Nettfrekvensen	50/60 Hz
Driftfrekvens	50/60 Hz

DIMENSJONER & VEKT



Lengde	49 mm
Bredde	48,00 mm
Bredde (inkl. runde armaturer)	48.00 mm
Høyde	22,00 mm
Høyde (inkl. sylindriske armaturer)	22.00 mm
Produktvekt	40,00 g

FARGER & MATERIALER

Produktfarge	Lysegrå
--------------	---------

TEMPERATURER & DRIFTSFORHOLD

Omgivelsestemperatur-område	-20...+60 °C
-----------------------------	--------------

YTTERLIGERE PRODUKTINFORMASJON

Antall styreutganger	1
Antall tilkoblede sensorer	4
Maks. tilkoblede trykknapptilkoblinger / sensorer	4
Idriftssettelses App	App (Android/iOS)
Grupper	4

MULIGHETER

Dimbar	Nei
--------	-----

Dimmingsgrensesnitt	DALI
Installasjons type	Armaturintegrering/Integrert i innfelt enhetsboks
Senderens rekkevidde	15 m

SERTIFIKATER & STANDARDS

Godkjenningssmerke - godkjenning	CE
Beskyttelsesklasse	II
Beskyttelses type	IP20

Utstyr/tilbehør

– Free App for iOS and Android available at the app store

NEDLASTNINGER

Dokumenter og sertifikater		Dokumentnavn
	Bruerveiledning / sikkerhetsinstrukser	DALI ACU BT Control
	Utvidet installasjonsveiledning	DALI ACU BT Control
	Samsvarserklæringer	DALI ACU BT
	Samsvarserklæringer UKCA	DALI ACU BT UK
	Sertifikater	VDE
	EU Data Act	Connected Products and Related Software and Services

LOGISTIKK INFORMASJON

Produktkode	Forpakkings enhet (stk/enhet)	Dimensjoner (lengde x bredde x høyde)	Bruttovekt	Volum
4052899544819	Folding box 1	81 mm x 81 mm x 46 mm	57.00 g	0.30 dm³
4052899544826	Shipping box 60	344 mm x 254 mm x 278 mm	3847.00 g	24.29 dm³

Den nevnte produktkoden beskriver den minste enheten som kan bestilles. En kartong kan inneholde ett eller flere enkeltprodukter. Når du legger inn en bestilling, vennligst oppgi antall kartonger som ønskes.

ANSVARSRASKRIVELSE

Endres uten varsel. Sørg alltid for å bruke den nyeste versjonen.